

TUFT-EMBROIDERING MACHINE

Patent Number: JP7090766
Publication date: 1995-04-04
Inventor(s): IWATA SUSUMU
Applicant(s): BARUDAN CO LTD
Requested Patent: JP7090766
Application Number: JP19930259416 19930921
Priority Number(s):
IPC Classification: D05C15/16; D05C15/22; D05C15/24
EC Classification:
Equivalents:

Abstract

PURPOSE: To provide a tuft-embroidering machine capable of moving a cloth in an arbitrary direction and of forming a free embroidery pattern.

CONSTITUTION: A tuft-embroidering machine is equipped with a vertically movable needle 4 for vertically carrying a yarn through a cloth 3 put on a needle location 1a, with a laterally movable looper 11 for scooping the yarn carried on the lower side of the cloth by the downward movement of the needle, with a yarn-cutting means 30 for cutting the yarn scooped with the looper at a place near to the looper, and furthermore with a yarn-holding means 16 for holding the yarn scooped with the looper at a place nearer to the needle than a position at which the yarn will be cut with the cutting means.

Data supplied from the esp@cenet database - I2

Patent Abstracts of Japan

PUBLICATION NUMBER : 07090766
PUBLICATION DATE : 04-04-95


APPLICATION DATE : 21-09-93
APPLICATION NUMBER : 05259416

APPLICANT : BARUDAN CO LTD;

INVENTOR : IWATA SUSUMU;

INT.CL. : D05C 15/16 D05C 15/22 D05C 15/24

TITLE : TUFT-EMBROIDERING MACHINE



ABSTRACT : PURPOSE: To provide a tuft-embroidering machine capable of moving a cloth in an arbitrary direction and of forming a free embroidery pattern.

CONSTITUTION: A tuft-embroidering machine is equipped with a vertically movable needle 4 for vertically carrying a yarn through a cloth 3 put on a needle location 1a, with a laterally movable looper 11 for scooping the yarn carried on the lower side of the cloth by the downward movement of the needle, with a yarn-cutting means 30 for cutting the yarn scooped with the looper at a place near to the looper, and furthermore with a yarn-holding means 16 for holding the yarn scooped with the looper at a place nearer to the needle than a position at which the yarn will be cut with the cutting means.

COPYRIGHT: (C)1995,JPO